

# GHH RAND

HOME

## CS700 Compact

Properties	Measurement Unit	Value
Medium	atmospheric air*	
Compressor suction volume stream (at 2,0 bar(g)) min.	m3/hr	290
Compressor suction volume stream (at 2,0 bar(g)) max.	m3/hr	720
Package input speed (standard execution) min.	rev/min.	1000
Package input speed (standard execution) max.	rev/min.	2000
Angular gear unit ratio	i=	1
V-belt drive ratio	i=	
Compressor speed min.	rev/min.	1000
Compressor speed max.	rev/min.	2000
Absorbed power at compressor shaft max	kW	48
Length	mm	440
Width	mm	750+360
Height	mm	650
Weight	kg	306

\*)suction temperature: 20° C, suction pressure: 1 bar (abs.)

© 2009 Ingersoll-Rand Company, All rights reserved.

"As an Ingersoll Rand business partner, you are representing a company committed to conducting business with the highest ethical standards. If you suspect an Ingersoll Rand employee of conducting business unethically or witness other misconduct, we ask that you report such activities to the Ethics and Compliance Group at [ethics@irco.com](mailto:ethics@irco.com). You may also report such matters anonymously by calling (collect if you wish) our Ethics HelpLine at +1-704.556.7046 from anywhere in the world."